



CHEM FLOWTRONICS

Stainless Steel In-Line Reduced Flow Reflux Splitters



AUTOMATIC or MANUAL REFLUX RATIO CONTROL

- Precise Split — very low hold-up
- High power solenoid
- 35 gpm model
- Automatic controller
- Only one moving part
- Fail-safe design
- Adaptable to any size column
- Interchangeable
- Easily maintained

FOR BATCH OR CONTINUOUS SYSTEMS

- External mounting on collector makes splitters interchangeable; allows simple inspection and service.
- Standard design provides reflux on power failure. (Total product take-off optional)
- Rigid stainless steel tongue assures positive shut-off.
- Collectors available in standard and extra low ΔP design for vacuum service.

ELECTRICAL CHARACTERISTICS

115-125 volts, 50-60 Cycles

1" size - 0.3 amps

2" size - 0.5 amps

Explosion proof or general purpose enclosures

PRESSURE RATING: FV-150 psi (300 psi optional)

TEMPERATURE: 450°F

CONSTRUCTION MATERIAL: Type 316 Stainless steel (other materials on request).



CHEM FLOWTRONICS

Chem Flow Corporation
P.O. Box 4635, Wayne NJ 07474-4635
Tel: 800-486-3356 · 973-785-0001
Fax: 973-785-8051
Email: info@chem-flowtronics.com
Web: www.chem-flowtronics.com

